








HOW TO PREPARE THE WALL FOR MAGNETIC COMBINATIONS

Product	Structure	Thickness (micron)	Finish	Product Code	Width (mm)	Lenght (m)	Pull (g/cm ²)	Features	Printability
MAGNETIC&FERRO Roll self-adhesive - for professional applications									
MAGNET ADHESIVE	MAGNET Plain brown with adhesive	500	matt	MGSA-6150-BR	615	20	28-30	To receive printed Ferro Film	-
		600	matt	MGSA-6015-BR	615 - 1020	15	34-36		-
	MAGNET white PVC with adhesive	600	matt	MGSA-10260-WM	1020	15	28-30		 
FERRO ADHESIVE	FERRO Plain brown with adhesive	250	matt	MGSFSA-1022530-BR	1020	30	-	To receive printed Magnet Film	-
		500	matt	MGSFSA-10250-BR	1020	15	-		-
	FERRO white PVC with adhesive	600	matt	MGSFSA-10260-WM	1020	15	-		  



- We highly recommend to clean up the wall or panel surface carefully, to ensure the best performance of the self-adhesive backing.
- The wall or panel surface must be well dried whatsoever.
- Heat gun use is suggested in order to soften the compound, revive the glued backing and improve the overall adhesion of the film to the designated surface.

 **Printability:**

 Eco-solvent, test recommended

 UV- TESTS RECOMMENDED

 Screen