

HOW TO PREPARE THE WALL FOR MAGNETIC COMBINATIONS

Product	Structure	Thickness (my)	Finish	Product code	Width (mm)	Length (m)	Pull (g/cm ²)	Features	Printability
MAGNET&FERRO Self-adhesive roll - for professional applications									
MAGNET ADHESIVE	MAGNET brown with adhesive	500	matt	MGSA-6150-BR	615	20	28-30	To receive printed Ferro Film	-
		600		MGSA-6015-BR	615 - 1020	15	34-36		
	MAGNET white PVC with adhesive			MGSA-10260-WM	1020	15	28-30		E U SC
FERRO ADHESIVE	FERRO brown with adhesive	250		MGSFSA-1022530-BR	1020	30	-	To receive printed Magnet Film	-
		500		MGSFSA-10250-BR		15	-		
	FERRO white PVC with adhesive	600		MGSFSA-10260-WM	1020	15	-		E U SC



- We highly recommend to clean up the wall or panel surface carefully, to ensure the best performance of the self-adhesive backing.
- The wall or panel surface must be well dried whatsoever.
- Heat gun use is suggested in order to soften the compound, revive the glued backing and improve the overall adhesion of the film to the designated surface.

Product	Structure	Thickness (my)	Finish	Product code	Pull (g/cm ²)	Size (cm)	Sheets (x box)	Features
Magnet Sheets - self-adhesive - easy to apply								
SELF-ADHESIVE MAGNET SHEETS	MAGNET brown with foam adhesive	500	brown	MGSA-30-FM	28-30	30*60 cm	50	To install easily magnetic walls and display on irregular surfaces
						30*45 cm	30	to be combined with Mr. Magnus Ferro on irregular surfaces
	MAGNET brown with adhesive	600		MGSA-30-BR	34-36	30*60 cm	50	To easily install magnetic walls and display
						30*45 cm	30	to be combined with Mr. Magnus Ferro

Product	Finish	Product code	Litre (l)	Peso (Kg)	Printability
FERRO PAINT - Magnetic receptive coating for wall					
	FERRO PAINT	black matt	PAINTWALL-08	1 L/can	1,6
					to receive printed magnetic film

<p>Where to use:</p> <p>Retail environments, classrooms, children's rooms, kindergartens, bedrooms, offices, recreation centers, museums, furniture surfaces, kitchens, bars and restaurants, etc.</p>	<p>Product Features Magnetic Receptive Surface:</p> <ul style="list-style-type: none"> • The ferro paint is not magnetic. It is magnetic receptive. • 100% water based, easy to apply and easy to clean • Low odor, no VOC, non-toxic and lead free. • Will not cause interference with electronic devices.
<p>Note: The ferro paint used as a primer. It can't hold heavy magnets. It goes best with flexible magnets with a large contact surface like magnetic cards and flat frid-gemagnets. Clean the can and application tools with water. Store the paint at temperature of 0° to 50° and avoid direct sunlight.</p>	

MAGNET&FERRO

for Panel and Wall set-up

THE RIGHT WAY TO CHANGE YOUR WALL DECORATION IN 6 MINUTES

Product	Structure	Thickness (my)	Finish	Product code	Width (mm)	Length (m)	Features	Printability
FERRO Film - Roll for Digital Printing and Overlapping								
FERRO FILM (ferrous) 	white PET	200	matt	PET-FSV20	1070 - 1270 1370 - 1520 - 1620	30	To be printed and applied on magnetic wall (multiple overlapping) display and packaging	E L U
	white PP	240		PP-FSV24	1070 - 1370 1620			
	white PP latex-UV			PPF-UL	1370 - 1620	50		L U
	Paper	180		PAP-FVM-05	1050	30		

Product	Structure	Thickness (my)	Finish	Product code	Width (mm)	Length (m)	Pull (g/cm ²)	Features	Printability
MAGNET Film - Roll for Digital Printing and Overlapping									
MAGNET FILM 	MAGNET WHITE PET ultra FLAT	300	matt	PETMG-30-WM	1070 - 1270 1370 - 1600	30	8-10	 To be applied on the Ferro Wall	E L U SC
	MAGNET WHITE PET industrial	300		PETMG-30-UL	1370 - 1600	50	8-10		L U SC
	MAGNET WHITE PVC for Digital & Screen Printing	400		MG-40-WM	500 - 1020	15	15-18		E L U SC
		500		MG-50-WM	615 - 1000	15	18-22		E U SC
		600		MG-60-WM	615 - 1000	10/15	28-30		



Printability:

Eco-solvent
 Latex
 Latex, test recommended
 UV
 Screen