




## MAGNET&FERRO FOR PANEL AND WALL SET-UP

### HOW TO PREPARE THE WALL FOR MAGNETIC COMBINATIONS

Product	Finish	Product Code	Structure	Thickness (µm)	Width (mm)	Length (m)	Pull (g/cm <sup>2</sup> )	Features	Printability
<b>MAGNET AND FERRO SELF-ADHESIVE ROLLS   For professional applications</b>									
MAGNET ADHESIVE	matt	MGSA-6150-BR	MAGNET brown with adhesive	500	615	20	28-30	to receive printed Ferro Film	-
		MGSA-6015-BR			615 - 1020	15	34-36		
		MGSA-10260-WM	MAGNET white PVC with adhesive	600	1020		28-30		
FERRO ADHESIVE		MGSF-SA-10250-BR	FERRO brown with adhesive	500	1020	15	-	to receive printed Magnet Film	
		MGSF-SA-10260-WM	FERRO white PVC with adhesive	600					


1. We highly recommend to clean wall or panel surface carefully, to ensure the best performance of the self-adhesive backing.
2. The wall or panel surface must be completely dry.
3. Use of a heat gun is recommended in order to soften the compound, revive the glued backing and improve the overall adhesion of the film to the designated surface.

Product	Finish	Product Code	Structure	Thickness (µm)	Pull (g/cm <sup>2</sup> )	Size (cm)	Sheets (per box)	Features
<b>MAGNET SHEETS   Self-adhesive, easy to apply</b>								
SELF-ADHESIVE MAGNET SHEETS	brown	MGSA-30-FM	Magnet brown with foam adhesive	500	28-30	30*60	50	to easily install magnetic walls and display on irregular surfaces
						30*45	30	to be combined with Mr. Magnus Ferro on irregular surfaces
		MGSA-30-BR	Magnet brown with adhesive	600	34-36	30*60	50	to easily install magnetic walls and display
						30*45	30	to be combined with Mr. Magnus Ferro

Product	Finish	Product Code	Litre (l)	Weight (kg)	Features	
<b>FERRO PAINT   Magnetic receptive coating for walls and panels</b>						
	FERRO PAINT	black matt	PAINTWALL-08	1 L / can	1,6	to receive printed magnetic film

#### WHERE TO USE:

Retail environments, classrooms, children's rooms, kindergartens, bedrooms, offices, recreation centres, museums, furniture surfaces, kitchens, bars and restaurants, etc.



#### PRODUCT FEATURES:

1. The ferro paint is not magnetic. It is magnetic receptive
2. 100% water based, easy to apply and easy to clean
3. Low odour, no VOC, non-toxic and lead free
4. Will not cause interference with electronic devices






#### Note:

The ferro paint, used as a primer, cannot hold heavy magnets. It is best suited to flexible magnets with a large contact surface, like magnetic cards and flat fridge magnets. Clean the can and application tools with water and store the paint at a temperature between 0°C and 50°C. Avoid direct sunlight.



### THE RIGHT WAY TO CHANGE YOUR WALL DECORATION QUICKLY & EASILY

Product	Finish	Product Code	Structure	Thickness (µm)	Width (mm)	Length (m)	Features	Printability
FERRO FILM   Rolls for Digital Printing and multiple overlapping								
FERRO FILM (ferrous) 	matt	PET-FSV20	white <b>PET</b>	200	1070 - 1270 1370 - 1620	30	to be printed and applied on magnetic surfaces (multiple overlapping) display and packaging	<b>E L U</b>
		PP-FSV24	white <b>PP</b>	240	1070 - 1370 1620	30		<b>L U</b>
		PPF-UL	white <b>PP</b> latex-UV		1370 - 1620	50		

Product	Finish	Product Code	Structure	Thickness (µm)	Width (mm)	Length (m)	Pull (g/cm <sup>2</sup> )	Features	Printability
MAGNET FILM   Rolls for Digital Printing and overlapping									
MAGNET FILM 	matt	PETMG-30-WM	MAGNET <b>WHITE PET</b> ultra FLAT	300	1070 - 1270 1370 - 1600	30	8 - 10	 to be applied on the Ferro Wall	<b>E L U SC</b>
		MGD-40-WM	Magnet <b>WHITE PVC</b> for Digital & Screen Printing	400	500 - 1020	15	15-18		<b>U SC</b>
		MG-50-WM		500	615 - 1000	15	18-22		
		MG-60-WM		600	615 - 1000	10/15	28-30		



Find out how we produce Magnet & Ferro!



Printability: **E** Eco-solvent **L** Latex **U** UV **SC** Screen